



## تیشو پروسسور

**POOYAN MK2250**

مشخصات و ویژگی ها:

- سهولت کاربری با صفحه نمایشگر لمسی به زبان فارسی و انگلیسی
- سیستم ارسال پیامک SMS جهت اعلام وضعیت نمونه ها در هر لحظه
- مجهز به باتری قابل شارژ جهت محافظت از بافت ها در برابر خشک شدن در زمان قطع برق
- کنترل، تنظیم و مشاهده دمای ظروف پارافین بصورت جداگانه و دائمی
- دارای تاخیر زمانی قابل تنظیم در شروع عملیات از یک دقیقه تا ۷۰ روز
- تنظیم زمانهای ظروف از ۱ دقیقه تا ۱۰۰۰۰ دقیقه
- امکان ایجاد مکث در حین پروسه جهت اضافه نمودن نمونه و یا جابجایی ظروف
- دارای زمان تاخیری جهت جلوگیری از سرایت محلول یک ظرف به ظرف دیگر
- مجهز به سیستم همزن در داخل ظروف
- دارای دو حالت عملکرد دستی و اتومات
- ظرفیت آماده سازی بیش از ۱۰۰ بافت در قالب تیشوتک در یک سیکل کامل
- ظروف ۱/۸ لیتری از جنس نشکن
- نصب تجهیزات حفاظتی و ایمنی
- تولید و کنترل کیفی دستگاه مطابق با استانداردهای IEC60601-1-2 , IEC61010-1 , ISO13485

## Technical specification

### Electrical specification

|                   |                |
|-------------------|----------------|
| Nominal voltage   | 220 / 240 V AC |
| Nominal frequency | 50 / 60 Hz     |

### weight

|            |      |
|------------|------|
| dry weight | 45Kg |
|------------|------|

### Dimensions

|          |           |
|----------|-----------|
| Diameter | 710mm     |
| Height   | 470-620mm |

### Programs

|                               |                      |
|-------------------------------|----------------------|
| Number                        | 9, freely selectable |
| Infiltration time per station | from 0 m to 9999 m   |
| Delayed start                 | without time limit   |

### Wax baths

|                         |               |
|-------------------------|---------------|
| Number                  | 2 (3optional) |
| Capacity                | 1.8L          |
| Temperature range       | 55-70 °C      |
| Overtemperature release | 75 °C ± 4 °C  |

### Reagent containers

|          |       |
|----------|-------|
| Number   | 10(9) |
| Capacity | 1.8L  |

### Cassettes baskets

|                   |                       |
|-------------------|-----------------------|
| Number of baskets | 2                     |
| Basket capacity   | approx. 100 cassettes |



پردازشگر بافت پویان



متعلقات دستگاه