

ULTRA [ARRAY] PROCESSING SINA

کاتنتت سرور راديو دیجيتال

Digital Radio Content Server (DRM) DRM-CS-V1



ETSI TS 101 968

ETSI TS 102 820

ETSI TS 102 821

Audio Source Coders:

- AAC(with and without SBR), CELP and HVXC
- Support Stereo and Mono Coding
- Support all DRM Bit-Rates
- Support all DRM Sampling Rates

Support MSC, SDC and FAC Structures

Support SDC Features: (Label, Audio/Application/FAC info, Date, Time, Language, Country and AFS)

Support DRM Data/File Applications (MOT,TDC, sync, async)

Support DRM DATA/Audio input Channels

Support DRM-MDI Protocol

Support Dynamic Reconfiguration and Scheduler

User friendly Windows like control panel

Remote Control and Monitoring

Inputs:

- 1 Stereo Balanced Analog Signal (XLR)
- 1 Audi Jack
- 1 Digital Audio S/PDIF Connector
- 10/100 Ethernet (TCP/IP) for Data/File stream input
- 10/100 Ethernet (TCP/IP) and V.24/RS232 for Remote Control and Configuration

Outputs (MDI):

- V.24/RS232 async. Serial Port for data transfer
- 10/100 Ethernet (TCP/IP) for data transfer

Cassis: Industry Standard 19" rack-mountable

Power: 90-260 VAC, 50-60 Hz Single Phase

آدرس : تهران - بیمارستان امام خمینی - ساختمان مرکز رشد تجهیزات و فناوری های پزشکی

تلفن : ۰۲۱-۶۶۹۰۷۵۱۶