

پمپ فشار بالای تک سیلندر

High Pressure Single Pump (JSSP-10000SS)



Apex technologies co., designed and manufactured a new compact generation of screw pump (up to 22000 psi with minimum flow rate of 0.001 cc/min with volume resolution of 0.0001 cc) assembly includes a pump body having an axial bore defining a travel chamber and a pressure chamber enable the operator to pump almost anything! These new single high pressure pumps are designed for applications requiring accurate pulseless flow and pressure control of different fluids such as:

- Core Flooding
- Reactant Feeding
- Supercritical Fluids
- HPLC and Ultra-HPLC
- Alternative Energy – Biomass



These pumps deliver specified pressure, flow rate and volume at both ambient and reservoir conditions and can operate at both constant pressure and constant flow rate. In the former mode, a pre-defined specific volume can accurately be transferred. Pressurization is obtained via a servo motor-driven piston. The pump is equipped with an extreme accurate pressure sensor (0.01 % full scale), two hand-operated valves for tank feeding and outlet delivery, a control panel and a storage tank. Optionally, a computer data acquisition and supervision system can be provided. Furthermore, a variable temperature heating mantle can be supplied to heat the fluid up to 150°C. These pumps can be customized based on the client requirements. For example, although standard material for wetted parts and volume are stainless steel and 500 cc, hastelloy can be requested for corrosive fluid applications and different volumes can be ordered.

Technical Specifications:

- ✓ Keller Pressure accuracy (10000 psi): 0.01 % full scale
- ✓ Maximum injection pressure: 10000 psi
- ✓ Pressure transmitters ×1 (10000 psi)
- ✓ Constant flow and pressure modes
- ✓ Wetted parts: Stainless steel 316L
- ✓ Minimum flow rate: 0.01 cc/min
- ✓ Maximum flow rate: 15 cc/min
- ✓ Cylinder volume: 500 cc
- ✓ Stable injection
- ✓ Weight: 48 kg