

Laboratory Freeze Dryer

The FD Series is a laboratory freeze-dryer specially developed for **basic** research in biotechnology and scientific institutes.

General features

Bench mounted table-top unit:It houses the refrigeration system and the vacuum pump.
Constructed in a steel stove enamelled cabinet with front door for maintenance purposes
-Air-cooled refrigeration system : Hermetically sealed.
Ozone friendly refrigerant.
-A top transparent acrylic lid provides viewing of the ice forming process
-PLC controlled system: a digital screen gives direct read-out of current condenser and vacuum temperatures during

the various stages of the cycle.

Model FD-5005-BT



Specifications	Model FD-5005-BT
Condenser Temperature	- 50°C
Condenser Capacity in 24 Hours	5 L
Overall Condenser Capacity	14 L
Condenser Type	Internal Coil (316 Stainless Steel)
System Refrigerant	CFC-Free
Defrost Method	Manual
Controller (Automation)	PLC Base LCD 3.7 inches
Vacuum Indication	Atmosphere to 0.001 Millibar
PC Interface	RS485(Option)
Outer Dimensions: W x D x H*	800 x 650 x 380mm
Weight	50 kg

*Address:*Tehran.ayatollah saeeid highway.chahardangeh industrial.town 19th street.4th felztarash.st. NO.24

220V/50

Accessories	Description
Chamber Dryer	Chamber 300 mm ϕ , with 3 trays
	(for vials, serum bottles and raw material)
10Port Manifold	Silicon tube manifold 10
Ampoule cannector	
8 Port Manifold	Including 8 rubber three way valves for flasks
Vacuum Pump	Rottary Oil Vacuum Pump
Stoppering Chamber (Option)	Glass cylindrical chamber with 3 non
	thermostatized shelves and manual vial closing
	device. Includes 3 trays
	(for vials and serum)
Vacuum Valve	Rubber three way valves for flasks



Chamber Dryer



Vacuum Pump



Vacuum Valve

8 Port Manifold



Stoppering Chamber

(Option)



10 Port Manifold Ampoule cannector (Option)

Address: Tehran, ayatollah saeeid highway, chahardangeh industrial, town 19th street. 4th felztarash, st. NO.24