

RasaAndishan Moj Pardaz

رساندیشان موج پرداز (دانش بنیان)



طراح و سازنده انواع آشکارسازهای خطی و دوربین های تصویربرداری

- Robust & Reliable Hardware & Software Architecture
- Multi Interface Connectivity (USB2.0,USB3.0,Ethernet)
- Cross Platform - Linux & windows Application Support
- Plugin Based API and Sophisticated FlowGraph Structure
- VariousSDK(C#,C++,MATLAB,VB.Net,Python,LabVIEW)Included



RA-ASC-0206



Overview

RA-ASC-0206 is a USB3.0 Bus Powered Area Scan Camera that incorporates a 4608 x 3456 Pixels CMOS array with Pixel Size of 1.34 μm by 1.34 μm .

It is capable of detecting light in the 400 - 700 nm range.

The Frame rate of This cost effective Color Area scan camera is up to 16 Hz.

This camera Supports External Triggering at rate of up to 16 Hz.

GUI Features

Operates up to 2 Cameras Simultaneously without loss of any data


Cross Platform Software with Auto-Detection of Compatible Cameras

Recording @ Predefined Counts, Time, Cache Size and Capture Size

Best Responsiveness by Separate Threads of Data Acquisition, Processing and Monitoring

Application


RA-ASC-0206 is Designed for Applications in Optics, Imaging, Biology, Digital Image Correlation(DIC), Industrial Process Control and General Laboratory Use.



Specification

Sensor Spec	
Sensor Type	Color CMOS Area Image Sensor
Light Spectrum	Visible
Pixel Size	1.34 um x 1.34 um
Pixel Height	1.34 um
Pixel Width	1.34 um
Effective Pixels	4608 x 3456
Image Resolution	16.35 MP
Image Size (HxV)	6.17 x 4.63 (mm)
Max Pixel Frequency	~270 MHz
Max Frame Rate	up to 16 Hz @ 16.35 MP
Shutter Type	Rolling Shutter
Exposure Control	✓
AOI Support	✓
Frame Rate @ AOI	up to 720 Hz @ 100 pixels x 100 pixels
Max Trigger Rate	up to 16 Hz @ 16.35 MP
Color Depth	8 Bit per Pixel
Brightness Coefficient	512 Analog Steps
Contrast Coefficient	1024 Analog Steps
Trigger Signal	TTL 5 V and 3.3 V
Trigger Mode	Free Running, Software Trigger, Hardware Trigger
Hardware Trig Polarity	Rising Edge, Falling Edge, Both Edges, High Level, Low Level
Trigger Factor	0 To 65535
Max Power Usage	3.5 Watt Without External Power Requirements
Min Trigger Pulse Length	33 ns
Trigger Delay	0 to 16 Min - in 1 us Steps
Interface	Super Speed USB 3.0 (2.6 Gbit/s)
Weight Dimension	80 gr (Without Lens) 42 mm x 42 mm x 29 mm
Temperature Range	- 48 to + 85 (°C)

رسا اندیشان موج پرداز (دانش بنیان)



حکیمیه، میدان فجر، خیابان خرم، خیابان سحر، کوچه پگاه ۶، پلاک ۱۱، واحد ۷

www.RasaAndishan.ir Info@RasaAndishan.ir ۰۲۱-۷۷۰۱۳۶۸۷