



Innovator In Spectroscopy Equipment

NEGATIVE PRECISION HIGH VOLTAGE -3KV 1mA MODEL NPHV2039X



NUCLEAR INSTRUMENTS MODULE



Innovator In Spectroscopy Equipment

NEGATIVE PRECISION HIGH VOLTAGE -3KV 1mA MODEL NPHV2039X

Features:

- Compact single width NIM package
- Regulated up to +5000 V dc 500 μ A output for negative and positive separately
- Noise and ripple \leq 10mV peak to peak
- Overload and short circuit protected
- Overload, inhibit status indicators
- Inhibit and overload latching circuits
- Four digit front panel meter
- CFP Instrument Control Bus (optional)
- LAN, USB, RS232, RS485 ICB available

Description:

The CFP Model 2039 High Voltage Power Supply is a single-width NIM module designed primarily for use with photomultiplier and electron multiplier tubes. But it can be used with any detector requiring a bias voltage up to 5000 V and a current level of 500 μ A or less.

The 2039 allows the user to select from two continuously adjustable outputs, ranging from +15 to +5000 V dc. The output voltage is measured and displayed by a four-digit voltmeter. In addition, this unit allows the user to has fully separately positive and negative output voltage polarity. The 2039 unit are fully arc and short circuit protected and will limit continuous short circuit output current to less than 150% of maximum rated output current.

Specifications:

Inputs

- Input Power: The Model 2039 is powered from a standard NIM Bin and power supply
- Inhibit: TTL Logic low or ground inhibits the HV outputs; max logic low \leq 0.4 V; logic high \geq 2.5 V.

Outputs

- HV Output: +15 to +5000 V dc, continuously adjustable, 500 μ A output current

Indicators

- HV Output: 4-digit panel meter 0 to 5000 V.
- Inhibit: LED indicates Inhibit status.
- Overload: LED indicates overload status.

Controls

- ON/OFF: Front panel toggle switch enables or disables output.
- Voltage: Front panel Multi turn controls switch continuous adjustment of the output voltage.
- Remote Control: Model 2039 have provisions for remote high voltage output control via an USB port.





Innovator In Spectroscopy Equipment

NEGATIVE PRECISION HIGH VOLTAGE -3KV 1mA MODEL NPHV2039X

Performance

- Voltage Regulation
 - Line: $\pm 0.001\%$ of rated output voltage for a $+1\%$ input line change
 - Load: $\pm 0.001\%$ of rated output voltage for a full load change
 - Ripple: See 10mVpp tabl
 - Stability: $\leq 0.005\%$ per hour, 0.02% per 8 hours, after a $\frac{1}{2}$ hour warm up
- Temperature
 - Temperature Coefficient: $\leq 50\text{ppm}/^\circ\text{C}$
 - Operating Temperature: 0°C to $+50^\circ\text{C}$
 - Storage Temperature: -40°C to $+85^\circ\text{C}$
 - Arc/Short Circuit: All units are fully arc and short circuit protected and will limit continuous short circuit output current to less than 150% of maximum rated output current.
- Other
 - Humidity: 20% to 85% RH, non-condensing
 - Interface Connector: LAN, USB, RS232, Rs485
 - Voltage: Front panel Multi turn control switch continuous adjustment of the output voltage.
 - Output Connector: SHV connector

Electrical and Mechanical Power Required:

Typical Power Requirements

- Standard version $+12\text{V} - 450\text{mA}$, $-12\text{V} - 450\text{mA}$

Physical

- Size: Single width NIM module $3.43 \times 22.12 \text{ cm}$ (1.35×8.71 inches) per TID-20893 (rev.) NET
- Weight: 0.9kg (2.0lbs.) - SHIPPING WEIGHT - 2.2 kg (4.9 lbs.)

Accessories Included

- LAN, USB, RS232, RS485 cable (opt)

NPHV2039D Rev1.0 10015-001



Model	Out put Voltage	Out put Current	Out put Number	Ripple (Vpp)
NPHV2039	0 to +500	0 to +8ma	2 POS	5mv
NPHV2039A	0 to +1000	0 to +4ma	2 POS	4mv
NPHV2039B	0 to +2000	0 to +2ma	2 POS	2mv
NPHV2039C	0 to +3000	0 to +1ma	2 POS	6mv
NPHV2039D	0 to +5000	0 to +500µa	2 POS	10mv
NPHV2039E	0 to +7500	0 to +250µa	2 POS	100mv



کنترل فرایند پاسارگاد

w w w . c f p . c o . i r