

| Model | FT150EA |
|------------------------------|---|
| Test Modes | <ul style="list-style-type: none"> • Pressure drop test • Air Permeability test • Filter efficiency test |
| Air flow | <ul style="list-style-type: none"> • 10...150 l/min ±2 % • Digital control |
| Control | <ul style="list-style-type: none"> • PLC control system • 7" HMI |
| Differential pressure | <ul style="list-style-type: none"> • 0...1200 Pa ± 2% |
| Media holder | <ul style="list-style-type: none"> • Circular exposed • Area: 100 cm² |
| Sensors | <ul style="list-style-type: none"> • Temperature, relative humidity |
| Tank pressure | <ul style="list-style-type: none"> • 1...8 bar |
| Air Dryer | <ul style="list-style-type: none"> • Air Line trap |
| Particle counter | <ul style="list-style-type: none"> • Laser Particle Counter • Flow rate: 2.8 L/min • Display six-channel particle sizes and particle concentration • Size channels: 0.3、0.5、1、3、5、10 (μm) • Built-in thermal printer |
| Aerosol Generator | <ul style="list-style-type: none"> • Aerosol: Atmospheric dust |
| Aerosol Dilutor | <ul style="list-style-type: none"> • Not Included |
| Power supply | <ul style="list-style-type: none"> • Single phase, 220V, AC |
| Weight | <ul style="list-style-type: none"> • Approx. 90 kg |

