

The FD Series is a laboratory freeze-dryer specially developed for basic research in biotechnology and scientific institutes.

## **General features**

the various stages of the cycle.

-Bench mounted table-top unit: It houses the refrigeration system and the vacuum pump. Constructed in a steel stove enamelled cabinet with front door for maintenance purposes -Air-cooled refrigeration system : Hermetically sealed. Ozone friendly refrigerant. -A top transparent acrylic lid provides viewing of the ice forming process -PLC controlled system: a digital screen gives direct read-out of current condenser and vacuum temperatures during



Specifications	Model FD-5005-BT
Condenser Temperature	- 50°C
Condenser Capacity in 24 Hours	10 L
Overall Condenser Capacity	32 L
Condenser Type	Internal Coil (316 Stainless Steel)
System Refrigerant	CFC-Free
Defrost Method	Manual
Controller (Automation)	PLC Base LCD 3.7 inches
Vacuum Indication	Atmosphere to 0.001 Millibar
PC Interface	RS485(Option)
Outer Dimensions: W x D x H*	800 x 650 x 380mm
Weight	75 kg
Standard Voltages	220V/50

<u>ADDRESS:</u> No 13,16/5 honar Alley,17 (Kaveh Bolvar) Street,Chahardange Industrial Area,Saeedy High Way ,Tehran,Iran Tel: (+98) 21 55 44 85 18<u>Telelfax</u>: (+98) 21 55 44 84 30 Denavacuum@gmail.com

ACCESSORIES	DESCRIPTION
Chamber Dryer	Chamber 300 mm Ø, with 3 trays (for vials and raw material)
8 Port Manifold	Including 8 rubber three way valves for flasks
Vacuum Valve	Rubber three way valves for flasks
Vacuum Pump	Rottary Oil Vacuum Pump
OPTION	
Stoppering Chamber	Glass cylindrical chamber with 3 non thermostatized shelves and manual vial closing

10 or 20 Port Manifold Ampoule cannecto

10 or 20 tube manifold Silicon

device. Includes 3 trays (for vials and serum)



**Vacuum Pump** 



**Chamber Dryer** 



**8 Port Manifold** 



**8 Vacuum Valve** 

Stoppering Chamber (OPTION) 20 Port Manifold Ampoule cannector ( OPTION)





<u>ADDRESS:</u> No 13,16/5 honar Alley,17 (Kaveh Bolvar) Street,Chahardange Industrial Area,Saeedy High Way ,Tehran,Iran Tel: (+98) 21 55 44 85 18<u>Telelfax</u>: (+98) 21 55 44 84 30 Denavacuum@gmail.com